
Note: This by-law received two readings only on April 25, 2006



# BY-LAW 2006-96

A By-law to amend By-laws 1229, 1442, 1507, 1767, 1914, 2053, 2150, 2237, 2284-68, 2402, 2489, 2551, 2571, 2612, 11-72, 122-72, 77-73, 83-73, 84-73, 119-73, 151-75, 88-76, 127-76, 250-77, 145-78, 162-78, 163-78, 184-78, 72-79, 91-79, 118-79, 134-79, 153-80, 165-80, 72-81, 90-81, 108-81, 193-81, 221-81, 28-82, 194-82, 196-82, 47-85, 304-87, 19-94 and 177-96, as amended by 28-97, as amended

THE COUNCIL OF THE CORPORATION OF THE TOWN OF MARKHAM HEREBY ENACTS AS FOLLOWS:

- By-laws 1229, 1442, 1507, 1767, 1914, 2053, 2150, 2237, 2284-68, 2402, 2489, 2551, 2571, 2612, 11-72, 122-72, 77-73, 83-73, 84-73, 119-73, 151-75, 88-76, 127-76, 250-77, 145-78, 162-78, 163-78, 184-78, 72-79, 91-79, 118-79, 134-79, 153-80, 165-80, 72-81, 90-81, 108-81, 193-81, 221-81, 28-82, 194-82, 196-82, 47-85, 304-87, 19-94 and 177-96, as amended as amended by By-law 28-97, be and the same is hereby further amended as follows:
  - 1.1 By adding to Section 2.0 of By-law 28-97, as amended, the following definitions, in alphabetical order:

"DWELLING, DUPLEX means a dwelling unit in a building that is divided horizontally into two dwelling units, each of which has an independent entrance either directly to the outside or through a common vestibule.

DWELLING, FOURPLEX means a dwelling unit in a building that is divided horizontally or a combination of vertically and horizontally into four dwelling units, each of which has an independent entrance either directly to the outside or through a common vestibule.

DWELLING, MULTIPLE means a dwelling unit in a multipleunit building.

GARAGE DOOR WIDTH means the width of the garage door opening(s), which is used for vehicular access. Where there is more than one opening, the garage door width shall be the distance between the two outer extremities of the garage door opening(s), including any intervening columns, doors, windows or wall sections which may separate two or more garage door opening(s).

LANDSCAPING, SOFT means that portion of a lot comprised of any combination of flowers, grass, shrubs, sod, trees or other horticultural elements that is not covered by architectural elements, asphalt, buildings, brickwork, concrete, stonework or structures.

MAIN WALL means the exterior front, side and/or rear wall of a building and all structural components essential to the support of a fully enclosed space.

**PARKING PAD** means an open area of land, other than a *driveway* that is paved and/or treated with a stable surface that is used for the parking of *motor vehicles*.

YARD, FRONT means a yard extending across the full width of the lot between the front lot line and the nearest main walls of the main building or structure on the lot.

**YARD** means an open, uncovered space on a *lot* appurtenant to a *building* and unoccupied by *buildings* or *structures* except as specifically permitted in this By-law.

YARD, EXTERIOR SIDE means the yard of a corner lot extending from the front yard to the rear yard between the exterior side lot line and the nearest main walls of the main building or structure on the lot.

YARD, INTERIOR SIDE means a yard other than an exterior side yard which extends from the front yard to the rear yard between the interior side lot line and the nearest main walls of the main building or structure on the lot."

- 1.2 By deleting subsection 6.2.4 and substituting the following:
  - "6.2.4 Driveway and Parking Pad Parking Provisions for Ground Oriented Residential Dwellings with Direct Motor Vehicle Access from a Public Street

Notwithstanding any other provisions of By-laws 1229, 1442, 1507, 1767, 1914, 2053, 2150, 2237, 2284-68, 2402, 2489, 2551, 2571, 2612, 11-72, 122-72, 77-73, 83-73, 84-73, 119-73, 151-75, 88-76, 127-76, 250-77, 145-78, 162-78, 163-78, 184-78, 72-79, 91-79, 118-79, 134-79, 153-80, 165-80, 72-81, 90-81, 108-81, 193-81, 221-81, 28-82, 194-82, 196-82, 47-85, 304-87, 19-94 and 177-96, as amended the provisions in this By-law shall apply to ground oriented residential dwellings, which for the purposes of this By-law are single detached, semi-detached, duplex, triplex, fourplex, multiple or townhouse dwelling units with direct motor vehicle access from a public street. All other provisions of these by-laws, unless specifically modified/amended by this By-law shall continue to apply.

- 6.2.4.1 General Parking Provisions for Ground Oriented Residential Dwelling Units
  - a) Within a front or exterior side yard motor vehicle parking is only permitted on a driveway or a parking pad.
  - b) A *driveway* associated with a ground oriented residential *dwelling* shall provide direct access to a *private garage*.
  - c) Within a front or exterior side yard there shall be no motor vehicle parking between an outside wall of an attached private garage, that faces a front or exterior side yard, and an interior side lot line.

### 6.2.4.2 Maximum Driveway Width

- a) The maximum *driveway* width shall be equal to the greater of:
  - i) the garage door width plus 1.5 metres; or
  - ii) 6.1 metres, provided a minimum 40% soft landscaping is provided in the front or exterior side yard that the driveway is located.

#### 6.2.4.3 Provisions for Parking Pads

- a) For the purposes of this By-law, where there is no private garage all areas on a lot accessible to motor vehicles shall be considered as parking pads.
- b) Where there is no *private garage* associated with a ground oriented residential *dwelling unit*, a *parking pad* is permitted, subject to the following:
  - i) the maximum *parking pad* width shall be the greater of:
    - a) 3.7 metres; or
    - b) 6.1 metres, provided a minimum 40% soft landscaping is provided in the front or exterior side yard that the parking pad is located.

## 6.2.4.4 Setbacks for Driveways or Parking Pads

- a) Driveways or parking pads that cross a front lot line and are used for the parking of motor vehicles shall be located:
  - no closer to an interior side lot line than the minimum distance requirement for the main building from the interior side lot line; and
  - ii) no closer to an exterior side lot line than the minimum distance requirement for the main building from the exterior side lot line.

- iii) Where a private garage is detached from the main building the driveway shall be located no closer to the exterior or interior side lot line than the minimum distance requirement for the detached private garage.
- b) Driveways or parking pads that cross an exterior lot line and are used for the parking of motor vehicles shall be located:
  - no closer to a rear lot line than the minimum distance requirement for the main building from the rear lot line; and
  - ii) no closer to a *front lot line* than the minimum distance requirement for the *main building* for the *front lot line*.
  - iii) Where a private garage is detached from the main building a driveway shall be located no closer to the rear lot line than the minimum distance requirement for the detached private garage.
  - iv) Where there is no private garage a parking pad shall be located no closer to the rear lot line than the minimum distance requirement for a detached accessory building.

### 6.2.4.5 Provisions for Circular Driveways

- a) On *lots* with frontages greater than 19.2 metres a second 3.7 metre wide *driveway* is permitted provided:
  - the main building is setback at least 8.0 metres from the street line;
  - ii) the driveways are at least 7.0 metres apart, at the street line;
  - iii) the second *driveway* connects the *public street* to the *driveway* that provides direct access from the *public street*.
- b) On lots with frontages between 16.8 metres and 19.1 metres a second 3.7 metre wide driveway is permitted provided:

- i) the *main building* is setback at least 8.0 metres from the *street line*;
- ii) the *driveways* are at least 7.0 metres apart at the *street line*;
- iii) both *driveways* are less than 3.7 metres wide; and
- iv) the second *driveway* connects the *public street* to the *driveway* that provides direct access from the *public street*.
- 6.2.4.6 Garages Facing an Interior Side Lot Line
  - a) When a garage door opening, used for *motor* vehicle access, faces an *interior side lot* line, the maximum driveway width in the front yard is 6.1 metres."
- 2.0 All other provisions of By-law 28-97, as amended, unless specifically modified/amended by this By-law continue to apply.

READ A FIRST AND SECOND TIME THIS  $25^{TH}$  DAY OF APRIL, 2006.

READ A THIRD TIME AND PASSED THIS...